

KENNEDY Bottle Jacks
QUALITY INDUSTRIAL TOOLING

With large cast iron bases with a steel cylinder housing and an adjusting notched saddle. Fitted with an overload protection valve. Two piece 'pumping' handle also operates hydraulic release. Use on a firm level surface. **DO NOT** work under the vehicle until another means of support, such as axle stands, are used. Models B234, B337 and B541 are supplied in a robust blow moulded carry case. **Complies with the EC Machinery Directive. GS and TUV approved.** (Load ratings are 'metric tonnes' i.e. 1 tonne = 1,000kg). All supplied with spare seals.

2, 3 and 5 tonne jacks supplied in a robust plastic case



Model Number	Max Load (Tonne)	Height (mm) Min. - Max.	Max Saddle Adjustment	Weight each	Order Code KEN-503	Offer Price/1
B234	2	181 - 345	48mm	3.00kg	-5820K	£12.99
B337	3	194 - 372	60mm	3.75kg	-5840K	£16.09
B541	5	216 - 416	70mm	4.90kg	-5860K	£20.43
B845	8	230 - 457	80mm	5.75kg	-5690K	£26.01
B1246	12	230 - 465	80mm	7.50kg	-5710K	£35.93
B1546	15	230 - 460	80mm	8.50kg	-5730K	£43.37
B2045	20	242 - 452	60mm	11.0kg	-5750K	£52.67

2 Tonne Low Profile Service Trolley Jack

Low Profile Trolley Jacks have strong, robust steel chassis to provide stability when under load. A low entry height. Heavy duty fixed direction castors and swivel castors ensure easy positioning under the vehicle prior to lifting. The pump handle with comfort rubber grip is to rapidly raise and lower the load arm and the vehicle. For use on a firm level surfaces. **DO NOT** work under the raised vehicle until another means of support, such as axle stands are in place.



Model Number	Maximum Load	Height (mm) Min. - Max.	Weight each	Order Code KEN-503	Offer Price/1
T5359	2000kg	89 - 359	14.5kg	-6520K	£40.94

2.5 Tonne Low Profile Trolley Jack

Low Profile Trolley Jacks have strong, robust steel chassis to provide stability when under load. A low entry height. Heavy duty fixed direction castors and swivel castors ensure easy positioning under the vehicle prior to lifting. The pump handle with comfort rubber grip is to rapidly raise and lower the load arm and the vehicle. For use on a firm level surfaces. **DO NOT** work under the raised vehicle until another means of support, such as axle stands are in place.



Model Number	Maximum Load	Height (mm) Min. - Max.	Weight each	Order Code KEN-503	Offer Price/1
T450L	2500kg	85 - 450	36kg	-6530K	£104.99

Heavy Duty Bottle Jacks

With machined/cast steel bases and cylinder housings. Fitted with an overload protection valve. Three piece 'pumping' handle also operates hydraulic release. Use on a firm level surface. **DO NOT** work under the vehicle until another means of support, such as axle stands, are used.



Model Number	Max Load (Tonne)	Height (mm) Min. - Max.	Max Saddle Adjustment	Weight each	Order Code KEN-503	Offer Price/1
B3047	30	285 - 475	-	23.0kg	-5770K	£102.27
B5048	50	300 - 480	80mm	34.0kg	-5790K	£136.37

2 Tonne Low Profile Long Reach Trolley Jack

Low profile long reach trolley jacks have strong, robust steel chassis to provide stability when under load. A low entry height. Heavy duty fixed direction castors, swivel castors and inside wheel ensure excellent manoeuvrability and easy positioning under the vehicle prior to lifting. The foot pedal is to rapidly raise and lower the load arm and the vehicle. The long reach pump handle has a comfort rubber grip. Includes a practical tray for carrying tools and a rubber pad for the saddle. For use on a firm level surfaces. **DO NOT** work under the raised vehicle until another means of support, such as axle stands are in place.



Model Number	Maximum Load	Height (mm) Min. - Max.	Weight each	Order Code KEN-503	Offer Price/1
T510L	2000kg	76 - 510	42kg	-6570K	£241.49
T525L	3000kg	140 - 525	50kg	-6580K	£304.49

Air Trolley Jack - 20/40T 2 Stage

For use when lifting heavy vehicles such as lorries etc. This industrial air jack has a robust steel chassis, 'T' bar handle with integral air control valve and two extensions for increased lifting height. It requires an air pressure of 116 - 174psi (8 - 12bar) and a supply rate of 105ltr/min (3.7cfm).



JTA2040
Air supply: 116 - 174psi (8 - 12bar).
Air consumption: 105ltr/min (3.7cfm).
Lifting capacity: 20T/40T.
Base height: 210mm.
Lifting height: 40T - 433mm, 20T - 520mm.
Air inlet size: 1/4NTP.

Model Number	Maximum Load	Height (mm) Min. - Max.	Weight each	Order Code KEN-503	Offer Price/1
JTA2040	40,00kg	210 - 520	74kg	-7120K	£629.99

HAND TOOLS